

Key Features

- High performance HF compression driver and LF woofer
- Rotary dispersion horn
- Minimally sized to be visually unobtrusive
- Pole Mount Cup
- 10 eye bolt suspension points
- Quick release fly track on top and bottom
- Asymmetric enclosure provides multiple mounting angles
- Rotatable logo
- Able to be used as a stage monitor



Specifications

The V15 is engineered to provide high definition, high output in a near field application. The V15 loudspeaker incorporates a 15" low frequency woofer and 1.77" voice coil high frequency compression driver. The woofer is mounted in a vented enclosure that is tuned for optimum low frequency response. The compression driver is mounted on a asymmetric rotatable horn with a dispersion angle of 80° and 50°.

The V15 has an asymmetric shape. It has a 45° angle for the speaker to be used as a floor monitor. It also has a 15° angle for ceiling mounting. The V15 also is equipped with a pole mount cup. The Fly track is used for a faster secure installation.

The system produces a frequency response is from 50Hz to 20KHz and is capable of producing a peak level of 128dB. The components inside the V15 are able to handle 500 watts of amplifier power and a peak power of 1000 watts.

Physical

	Model V15
System Configuration	2 way, Full Range
	LF 1x 15-in
	HF 1x 1-in exit 1.77-in voice coil compression driver on a Rotary Horn
Crossover	Passive
Frequency Response	70Hz-20KHz
Axial sensitivity 1w/1m	108dB
Power Rating	RMS 500W Peak 1000W
Finish	Black Textured Paint
Connectors	2x NL4
Hardware	10 Threaded mounting point, Fly track, Pole mount cup
Grille	Foam backed, Black powder coated grill
Dimensions	H 27.25" L 14.25" W 17.25"
Weight	63lb